


Presentation Overview FFTT Screen Design Principles Conceptual Fish Screen Proposals Information / Study Needs

Screen Design Principles Design and operate the intake in accordance with NMFS, and CDFG design criteria and USFWS guidance for an intake within the Delta where delta smelt and other sensitive fish species are present







BDCP

Screen Design Principles

Select locations that have desirable hydraulic characteristics (uniform sweeping velocities, reduced turbulence)

BDCP

Screen Design Principles

Select locations on the Sacramento
River as far north as possible to avoid
areas of the river with the greatest
susceptibility to tidal influence (i.e.
reverse or stagnant flow conditions)
in order to minimize fish exposure to
screens

BDCI

Screen Design Principles

Select locations on the Sacramento River as far north as practicable to reduce the exposure of delta smelt, longfin smelt, and other estuarine species

Screen Design Principles Avoid the need to collect, concentrate, and handle fish passing the intake

Screen Design Principles Avoid bypasses that concentrate fish and increase the risk of predation



Screen Design Principles Avoid creating areas where predators may congregate or where potential prey would have increased vulnerability to predation



Use multiple smaller intakes (as opposed to a single large intake) to enhance fish protection with operational flexibility under varying flow conditions

Screen Design Principles

Minimize the length of screen intake(s) to reduce the duration of exposure to the screen surface for fish




















































Information/Study Needs

Fish species presence, timing, and distribution for applicable life stages within the reach of the Sacramento River between the City of Sacramento and Walnut Grove

Information/Study Needs

Need current hydro-dynamics within the reach of the Sacramento River between Sacramento and Walnut Grove

Need detailed bathymetry

Need depth and velocity profile data for various locations

Information/Study Needs

Need to model the estimated changes to hydro-dynamics associated with the addition of the proposed diversion(s)

Effects of facility on channel flood carrying capacity

Additional analysis may include hydraulic and hydro-dynamic modeling, physical modeling, sediment modeling, 2 dimensional testing of baffle systems ('dynamic baffling'), and further analysis of delta smelt and green sturgeon interaction with fish screen designs.

Information/Study Needs

BDCP

Need to consider future hydrologic conditions associated with climate-change

Information/Study Needs

Need to consider any applicable
navigational and flood conveyance
regulations established by the
US Coast Guard and
US Army Corps of Engineers
that could affect placement of
in-river structures